

TECHNICAL DATA



	Insolation Monitor	control fuse	Stall Protection	Cable+Schuko 2pol .	Load secure 2 pol.	Combi for outside	Socket and hinged lid	Cotek WR Fremote	Dimensions cm
Trustec Insolation Monitor TiW									L X W X H
TiW 1 without load protection									
TiW 1- Plug-Protect	*	*	*	*	--		1	--	140x140x90
TiW1-Connect-Protect	*	*	*	--	--		1	--	140x140x90
TiW1 -Connect CR8	*	*	*	--	--		1	CR8	180x110x138
TiW 2 With load securing according to VDE¹									
TiW 2 2pol-VDE-cable termination	*	*	*		*		*	--	138x245x130
TiW 2-2pol-ST2	*	*	*		*		2	--	138x245x131
TiW 2 2pol-VDE-CR8-ST4	*	*	*		*		4	CR8	205x320x146
TiW 2 2pol-VDE-CR16-ST3	*	*	*		*		3	CR16	205x320x146
TiW 3 With load protection for mains outdoor / inverter connection switchover¹									
TiW 3 2pol-VDE--ST2	*	*	*		*	*	2	--	138x245x131
TiW 3 2pol-VDE-CR8-ST2	*	*	*		*	*	2	CR8	138x245x131
TiW 3 2pol-VDE-CR8-ST4	*	*	*		*	*	4	CR8	138x245x131

¹ Test- and Resetbutton inside / external Test- and Resetbutton optional)