

TECHNICAL DATA AND ACCESSORIES RESCUECHARGER IN 1X12A - 1X20A - 1X35A



RescueCharger	1 x 12 A	1 x 20 A	1 x 35 A
Item No. mit PlugIn	705600	706200	705000
Mains voltage VAC	230 V/50-60	230 V/50-60	230 V/50-60
Operating temperature	-35 bis + 50 °C	-35 bis + 50 °C	-35 bis + 50 °C
Charging voltage* S1 VDC	14,4	14,4	14,4
Float voltage S2 VDC	13,5	13,5	13,5
Charging current A	12	20	35
Recommended battery max. Ah	150	250	600
IP-rate	44	44	44
Weight kg	1	1,5	2
Height/Width/Depth mm	138 x 98 x 53	182 x 98 x 53	200 x 98 x 53

RescueCharger Accessories	
706483	2 m Charging cable 20 A
706484	4 m Charging cable 20 A
706485	6 m Charging cable 20 A
705099	2 m Charging cable 35 A
705147	4 m Charging cable 35 A
705159	6 m Charging cable 35 A
715160	8 m Charging cable 35 A
705294	5 m Remote Panel 1x20A,1x35A
705295	10 m Remote Panel 1x20A,1x35A
705296	20 m Remote Panel 1x20A,1x35A
705297	25 m Remote Panel 1x20A,1x35A
705463	Connection Schuko Plugin